

HELI-PUMP

PORTABLE ELECTRIC AVIATION PUMP



COMPACT, LIGHTWEIGHT AND PORTABLE

In use around the world by military special forces and helicopter operators, the Heli-Pump is a complete turnkey electric aviation fuel pumping system in a tiny package.

Designed for rapid deployment, the Heli-Pump quickly distributes fuel from almost any source and can be powered by the helicopter's DC system. It offers two-stage filtration, making it ideal for remote site operations.

When not in use, the Heli-Pump can be easily packed and stored inside the cargo area of most helicopters. Choose from a variety of models to suit your needs with ready-to-ship inventory of these pumps available.

REFUELING IN A TURNKEY PACKAGE

Practical standard features and a variety of models to choose from make the Heli-Pump ideal for many applications. Please see the reverse side for specific model specifications.

Features include:

- Monitor, filter, electric pump, plus intake and delivery hoses and a lightweight anti-drip nozzle.
- Operates from a vehicle battery or from the helicopter's own power supply.
- Electric supply cable with clamps for connection to the power supply and in-line fuse.
- Ground connection lug.
- Powder-coated aluminum roll cage.

Printed in Canada
Aug. 12, 2016 v2.5



HELI-PUMP MODELS

PORTABLE ELECTRIC AVIATION PUMP



SLIMLINE HELI-PUMP

- 10 USGPM (37 LPM) 24 VDC, 10 AMP electric pump
- Aviation spin-on filters
- Leak-proof hard carrying case with lock
- 12 ft. of 1" discharge hose with nozzle
- 12 ft. of 1" suction hose with camlocks
- Flow meter (GPM) or (LPM)
- Camlock connection drum stub
- 12 ft. grounding wire
- 12 ft. of electric cable (connection to battery)
- Water detection paste
- Pump dims without carrying case: 18" x 20.5" x 8.5" - 21 lbs (46 cm x 52 cm x 22 cm - 9.5 kg)
- Total pump dims with carrying case: 23.5" x 29" x 16" - 84 lbs (60 cm x 74 cm x 41 cm - 38 kg)

HR1210 HELI-PUMP

- 11 USGPM (41 LPM) 12 VDC, 25 AMP electric pump
- Filter/separator
- 12 ft. of 1" discharge hose with nozzle
- 12 ft. of 1" suction hose with camlocks
- Flow meter (GPM) or (LPM)
- Camlock connection drum stub
- 12 ft. grounding wire
- 12 ft. of electric cable (connection to battery)
- Water detection paste
- Pump dims: 20" x 23" x 17.5" - 60 lbs (51 cm x 58 cm x 45 cm - 27 kg)

HR 2410 HELI-PUMP

- 11 USGPM (41 LPM) 24 VDC, 10 AMP electric pump
- Filter/separator
- 12 ft. of 1" discharge hose with nozzle
- 12 ft. of 1" suction hose with camlocks
- Flow meter (GPM) or (LPM)
- Camlock connection drum stub
- 12 ft. grounding wire
- 12 ft. of electric cable (connection to battery)
- Water detection paste
- Pump dims: 20" x 23" x 17.5" - 106 lbs (51 cm x 58 cm x 45 cm - 48 kg)

HR2420 HELI-PUMP

- 20 USGPM (75 LPM) 24 VDC, 30 AMP electric pump
- Filter/separator
- 12 ft. of 1" discharge hose with nozzle
- 12 ft. of 1" suction hose with camlocks
- Flow meter (GPM) or (LPM)
- Camlock connection drum stub
- 12 ft. grounding wire
- 12 ft. of electric cable (connection to battery)
- Water detection paste
- Pump dims: 20" x 23" x 17.5" - 60 lbs (51 cm x 58 cm x 45 cm - 27 kg)

