



# JUNGLE KING GAS™

COLLAPSIBLE FABRIC PILLOW TANK

The Jungle King Gas collapsible tank is purpose-built for gasoline fuel storage in hot, humid, wet climates. Constructed from a multi-coated, high-durability fabric using SEI's proprietary PetroH2Ohesive™, the Jungle King Gas has an external coating with excellent UV and hydrolysis resistance and an internal coating, designed specifically for gasoline, that provides a longer life expectancy than any other urethane collapsible fabric tank in the jungle. The Jungle King Gas has a vent system to handle flash rainfalls and is ideally suited for even the most extreme jungle conditions. Jungle King Gas combines portability and versatility with economy. A full range of sizes are available from 250 to 30,000 USG.

## COLLAPSIBLE TANK FEATURES

- 100% RF (radio frequency) welded
- Fully collapsible
- Rapidly deployable
- Easy to fold, transport and relocate
- Requires minimal site preparation
- Lightweight – saves on transport costs
- Won't rust or corrode

## ADVANCED FABRIC FEATURES

- Exclusive Jungle King™ fabric exceeds US military specifications
- Hydrolysis resistant outer coating
- Gasoline compatible inner coating capable of handling up to 10% ethanol.
- Tank continually adjusts to any volume of liquid so that air cannot accumulate, reducing microbiological growth
- Fuel quality is preserved – extending equipment life and safety
- Also suitable for JP-1, JP-4, JP-8, kerosene and diesel fuels with less than 40% aromatic content
- 1-year manufacturer's warranty

SEI Industries can supply the Jungle King Gas as a stand-alone product or as part of a complete turn-key jungle fuel system:

- Primary storage tank with tropical vent
- Secondary containment berm
- Rainwater filter system
- Solar shade
- Fuel transfer, metering and filtration equipment

## JUNGLE KING GAS



SEI's Jungle King Gas collapsible fuel tank.



Each Jungle King Gas tank comes with test strips to verify on-going tank condition.

### JUNGLE KING GAS TANK SPECIFICATIONS

CAPACITY		MAXIMUM COLLAPSIBLE DIMENSION W X L		SHIPPING WEIGHT WITH CRATE		APPROX. SHIPPING CRATE DIMENSION	
USG	L	IN	CM	LB	KG	IN	CM
500	1900	85 x 119	220 x 300	148	68	36 x 38 x 17	92 x 97 x 43
1000	3800	96 x 181	240 x 460	195	89	36 x 38 x 17	92 x 97 x 43
1500	5700	119 x 181	300 x 460	232	106	48 x 48 x 12	122 x 122 x 26
2500	9500	162 x 181	410 x 460	279	127	48 x 48 x 12	122 x 122 x 26
3000	12000	165 x 214	420 x 540	285	130	48 x 48 x 18	122 x 122 x 46
5000	19000	193 x 238	490 x 610	376	171	48 x 48 x 24	122 x 122 x 61
7500	29000	207 x 300	530 x 760	434	197	48 x 48 x 36	122 x 122 x 92
10000	38000	243 x 300	620 x 760	527	239	48 x 48 x 40	122 x 122 x 102
12000	46000	266 x 300	680 x 760	590	269	48 x 48 x 40	122 x 122 x 102
15000	57000	271 x 362	690 x 920	606	275	48 x 48 x 40	122 x 122 x 122
20000	76000	314 x 382	800 x 970	800	364	48 x 48 x 48	122 x 122 x 122
24000	91000	314 x 438	800 x 1110	906	412	48 x 48 x 48	122 x 122 x 122
30000	114000	392 x 448	1000 x 1140	1158	527	48 x 84 x 30	122 x 213 x 76

Custom sizes available